Palmgren Floor-Standing & Bench Mounted Jointers

Featuring dustup

84261

84163

The cutterheads on these **6⅛" Jointers** use HSS blades that can be resharpened. The cast iron fence, infeed & outfeed tables provide stability and long life. Palmgren woodworking tools also feature *dustup*® the built-in dust & chip collection system that virtually eliminates airborne sawdust & clean-up.

Palmgren **Jointers** provide professional features and performance in a compact package. Joint and plane hardwoods or softwoods up to 6⅛". All work surfaces are ground for smooth, precise operation and the fence system slides across the table to use the entire width of the cutting blades. The fence & fence guide can be quickly adjusted from 45º inward to 45º outward, with positive stops at 45º & 90º for bevel & chamfer cuts. Large, locking paddle switch helps prevent unauthorized use.

6⅛" Bench-Mounted Jointer (#84261)

- Two blade cutterhead with HSS blades (blades can be resharpened).
- Adjustable cut depth on infeed table.
- 2 year warranty.
- Pre-drilled holes in base for mounting to bench or stand (Palmgren offers a heavy duty floor stand #70102, sold separately).

6⅛" Floor-Standing Jointer (#84263)

- Three blade cutterhead with HSS blades (blades can be resharpened).
- Adjustable cut depth on infeed & outfeed tables.
- ½" rabbeting capacity.
- 2 year warranty.

SKU	Motor	Cutterhead Cuts per Minute	Infeed & Outfeed Table Size	Max. Cut Depth in / mm	Fence Tilt (degrees)	Weight lb / kg
Jointers						
84261	1 HP Universal 120V (60 Hz) 12 Amps	20,000	13⅜ L x 6¼ W	⅛	45°, 90°, 135°	104
			346 L x 160 W	3		47
84163	1 HP Induction 120V (60 Hz) 12.2 Amps	14,100	22¾ L x 7¼ W	⅛	45°, 90°, 135°	204
			578 L x 184 W	3		96

For more info on DustUp® see page 1